



Prestone



SAFETY DATA SHEET

Holts Car Paints (Solid/ Block Colours)

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name	Holts Car Paints (Solid/ Block Colours)
Product number	HDRE01, HRE03, HCR05, HCR06, HCR07, HCR08, HCR09, HCR10, HCR11, HGREY01, HGREY02, HGREY03, HRE04, HGREY04, HDGREY01, HDGREY02, HDGREY03, HDGREY04, HBLK01, HBLK02, HBLK03, HWHI24, HRE05, HRE06, HRE07, HRE08, HRE09, HRE10, HRE11, HRE12, HDRE03, HRE13, HRE14, HRE15, HRE16, HRE17, HRE18, HRE19, HRE20, HRE21, HRE22, HDRE04, HDOR01, HOR01, HOR02, HOR03, HOR04, HOR05, HDYE01, HYE01, HYE02, HYE03, HDRE05, HYE04, HYE05, HYE06, HGR01, HGR02, HGR03, HDGR01, HDGR02, HDGR03, HDGR04, HDRE06, HNAV01, HNAV02, HNAV03, HNAV04, HNAV05, HNAV06, HNAV08, HNAV09, HDBLU01, HDRE07, HDBLU02, HDBLU03, HDBLU04, HDBLU05, HDBLU06, HBLU01, HBLU02, HBLU03, HLBLU01, HLBLU02, HDRE08, HLBLU03, HPI01, HLGREY01, HWHI02, HWHI03, HWHI04, HWHI05, HWHI06, HWHI07, HWHI08, HRE01, HWHI01, HWHI09, HWHI10, HWHI11, HWHI12, HWHI13, HWHI14, HWHI15, HCR01, HCR02, HRE02, HWHI16, HCR03, HCR04, HWHI17, HWHI18, HWHI19, HWHI20, HWHI21, HWHI22, HWHI23
REACH registration notes	This is a MIXTURE; no registration information contained in this document . Holts are classed as Downstream User.

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses	Paint.
------------------------	--------

1.3. Details of the supplier of the safety data sheet

Supplier	A Holts Car Care Product Holt Lloyd International Ltd Barton Dock Road Stretford Manchester M32 0YQ - England, UK +44 (0) 161 866 4800 FAX +44 (0) 161 866 4854 www.holtsauto.com
Contact person	Contact Email address: info@holtsauto.com

1.4. Emergency telephone number

Emergency telephone	UK - 00 44 (0) 161 866 4800 Office hrs = 0900 - 1700 hrs
National emergency telephone number	https://poisoncentres.echa.europa.eu/

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards	Aerosol 1 - H222, H229
Health hazards	Eye Irrit. 2 - H319 STOT SE 3 - H336

Holts Car Paints (Solid/ Block Colours)

Environmental hazards Not Classified

2.2. Label elements

Hazard pictograms



Signal word Danger

Hazard statements
 H222 Extremely flammable aerosol.
 H229 Pressurised container: may burst if heated.
 H319 Causes serious eye irritation.
 H336 May cause drowsiness or dizziness.

Precautionary statements
 P101 If medical advice is needed, have product container or label at hand.
 P102 Keep out of reach of children.
 P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P211 Do not spray on an open flame or other ignition source.
 P251 Do not pierce or burn, even after use.
 P261 Avoid breathing spray.
 P271 Use only outdoors or in a well-ventilated area.
 P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
 P501 Dispose of contents/ container in accordance with local regulations.

Contains ACETONE, BUTYL ACETATE -norm

Supplementary precautionary statements
 P264 Wash contaminated skin thoroughly after handling.
 P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
 P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P312 Call a POISON CENTRE/doctor if you feel unwell.
 P337+P313 If eye irritation persists: Get medical advice/ attention.
 P403+P233 Store in a well-ventilated place. Keep container tightly closed.
 P405 Store locked up.

2.3. Other hazards

The product does not contain any substance that is classified as PBT or vPvB

SECTION 3: Composition/information on ingredients

3.2. Mixtures

ACETONE	30-60%
CAS number: 67-64-1	EC number: 200-662-2
Classification	
Flam. Liq. 2 - H225	
Eye Irrit. 2 - H319	
STOT SE 3 - H336	

Holts Car Paints (Solid/ Block Colours)

BUTYL ACETATE -norm	10-30%
CAS number: 123-86-4	EC number: 204-658-1
Classification	
Flam. Liq. 3 - H226	
STOT SE 3 - H336	
DIMETHYL ETHER	10-30%
CAS number: 115-10-6	EC number: 204-065-8
Classification	
Flam. Gas 1 - H220	
Press. Gas	
BUTANE	10-30%
CAS number: 106-97-8	EC number: 203-448-7
Classification	
Flam. Gas 1 - H220	
Press. Gas	
2-METHOXY-1-METHYLETHYL ACETATE	5-10%
CAS number: 108-65-6	EC number: 203-603-9
Classification	
Flam. Liq. 3 - H226	
ISOBUTANE	1-5%
CAS number: 75-28-5	EC number: 200-857-2
Classification	
Flam. Gas 1 - H220	
Press. Gas	

The full text for all hazard statements is displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation	Move affected person to fresh air at once. Keep affected person warm and at rest. Get medical attention immediately.
Ingestion	Rinse mouth thoroughly with water. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Do not induce vomiting. Never give anything by mouth to an unconscious person. Do not induce vomiting.
Skin contact	Remove affected person from source of contamination. Get medical attention if any discomfort continues.
Eye contact	Remove affected person from source of contamination. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes and get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Holts Car Paints (Solid/ Block Colours)

4.3. Indication of any immediate medical attention and special treatment needed

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media Use fire-extinguishing media suitable for the surrounding fire.

5.2. Special hazards arising from the substance or mixture

Specific hazards Containers can burst violently or explode when heated, due to excessive pressure build-up.

5.3. Advice for firefighters

Protective actions during firefighting Move containers from fire area if it can be done without risk.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.2. Environmental precautions

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Wear suitable protective equipment, including gloves, goggles/face shield, respirator, boots, clothing or apron, as appropriate. Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation.

6.4. Reference to other sections

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Keep away from heat, sparks and open flame. Avoid spilling. Avoid contact with skin and eyes. Provide adequate ventilation. Avoid inhalation of vapours. Use approved respirator if air contamination is above an acceptable level.

7.2. Conditions for safe storage, including any incompatibilities

7.3. Specific end use(s)

SECTION 8: Exposure controls/Personal protection

8.1. Control parameters

Occupational exposure limits

ACETONE

Long-term exposure limit (8-hour TWA): WEL 500 ppm 1210 mg/m³

Short-term exposure limit (15-minute): WEL 1500 ppm 3620 mg/m³

BUTYL ACETATE -norm

Long-term exposure limit (8-hour TWA): WEL 150 ppm 724 mg/m³

Short-term exposure limit (15-minute): WEL 200 ppm 966 mg/m³

DIMETHYL ETHER

Long-term exposure limit (8-hour TWA): WEL 400 ppm 766 mg/m³

Short-term exposure limit (15-minute): WEL 500 ppm 958 mg/m³

BUTANE

Long-term exposure limit (8-hour TWA): WEL 600 ppm 1450 mg/m³

Short-term exposure limit (15-minute): WEL 750 ppm 1810 mg/m³

2-METHOXY-1-METHYLETHYL ACETATE

Long-term exposure limit (8-hour TWA): WEL 50 ppm(Sk) 274 mg/m³(Sk)

Short-term exposure limit (15-minute): WEL 100 ppm(Sk) 548 mg/m³(Sk)

Holts Car Paints (Solid/ Block Colours)

ISOBUTANE

Long-term exposure limit (8-hour TWA): OES 800 ppm

Short-term exposure limit (15-minute): OES 800 ppm

WEL = Workplace Exposure Limit

8.2. Exposure controls

Protective equipment



Eye/face protection

The following protection should be worn: Chemical splash goggles.

Hand protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. EN374 It is recommended that gloves are made of the following material: Rubber (natural, latex).

Other skin and body protection

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact.

Hygiene measures

Wash at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. Use appropriate skin cream to prevent drying of skin. When using do not eat, drink or smoke. Do not smoke in work area.

Respiratory protection

No specific recommendations. Respiratory protection may be required if excessive airborne contamination occurs.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	Aerosol.
Colour	Various
Flash point	Not applicable.
Upper/lower flammability or explosive limits	Lower flammable/explosive limit: 1.2% Upper flammable/explosive limit: 18.6%

9.2. Other information

Volatile organic compound This product contains a maximum VOC content of 726.2 g/litre.

SECTION 10: Stability and reactivity

10.1. Reactivity

10.2. Chemical stability

10.3. Possibility of hazardous reactions

10.4. Conditions to avoid

Conditions to avoid Avoid heat, flames and other sources of ignition. Avoid contact with acids and alkalis.

10.5. Incompatible materials

10.6. Hazardous decomposition products

Hazardous decomposition products Thermal decomposition or combustion products may include the following substances:
Thermal decomposition or combustion products may include the following substances: Acrid smoke or fumes. Carbon dioxide (CO₂). Carbon monoxide (CO).

SECTION 11: Toxicological information

Holts Car Paints (Solid/ Block Colours)

11.1. Information on toxicological effects

Inhalation	Vapours may cause headache, fatigue, dizziness and nausea. Extensive use of the product in areas with inadequate ventilation may result in the accumulation of hazardous vapour concentrations. May cause eye and respiratory system irritation. Symptoms following overexposure may include the following: Headache.
Ingestion	No harmful effects expected from quantities likely to be ingested by accident.
Skin contact	Prolonged and frequent contact may cause redness and irritation.
Eye contact	Irritating to eyes. Repeated exposure may cause chronic eye irritation.
Route of exposure	Inhalation Skin and/or eye contact

SECTION 12: Ecological information

Ecotoxicity	Not regarded as dangerous for the environment. The product components are not classified as environmentally hazardous. However, large or frequent spills may have hazardous effects on the environment.
--------------------	---

12.1. Toxicity

12.2. Persistence and degradability

12.3. Bioaccumulative potential

12.4. Mobility in soil

12.5. Results of PBT and vPvB assessment

12.6. Other adverse effects

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal methods	Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority. Empty containers must not be punctured or incinerated because of the risk of an explosion.
-------------------------	--

SECTION 14: Transport information

14.1. UN number

UN No. (ADR/RID)	1950
UN No. (IMDG)	1950
UN No. (ICAO)	1950
UN No. (ADN)	1950

14.2. UN proper shipping name

Proper shipping name (ADR/RID)	AEROSOLS
Proper shipping name (IMDG)	AEROSOLS
Proper shipping name (ICAO)	AEROSOLS
Proper shipping name (ADN)	AEROSOLS

14.3. Transport hazard class(es)

ADR/RID class	2.1
ADR/RID classification code	5F

Holts Car Paints (Solid/ Block Colours)

ADR/RID label	2.1
IMDG class	2.1
ICAO class/division	2.1
ADN class	2.1

Transport labels



14.4. Packing group

ADR/RID packing group	None
IMDG packing group	None
ICAO packing group	None
ADN packing group	None

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

14.6. Special precautions for user

EmS	F-D, S-U
ADR transport category	2
Tunnel restriction code	(D)

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78
and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations	The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (SI 2009 No. 716).
EU legislation	Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended). VOC Directive - 2004/42/EC Aerosol Dispensers Directive 2008/47/EC (2008/47/EC)

15.2. Chemical safety assessment

SECTION 16: Other information

Revision date	19/09/2019
Revision	2
Supersedes date	13/08/2012
SDS number	14502

Holts Car Paints (Solid/ Block Colours)

Hazard statements in full

H220 Extremely flammable gas.
H222 Extremely flammable aerosol.
H225 Highly flammable liquid and vapour.
H226 Flammable liquid and vapour.
H229 Pressurised container: may burst if heated.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.