



Prestone



SAFETY DATA SHEET Holts Headlight Sealer

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name	Holts Headlight Sealer
Product number	HREP0050A, HREP0029A, HREP0063A
UFI	UFI: PPA6-E0XS-F009-VR5E

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses	Car maintenance product.
-----------------	--------------------------

1.3. Details of the supplier of the safety data sheet

Supplier	A Holts Car Care Product Holt Lloyd International Ltd Barton Dock Road Stretford Manchester M32 0YQ - England, UK +44 (0) 161 866 4800 FAX +44 (0) 161 866 4854 www.holtsauto.com
Contact person	Contact Email address: info@holtsauto.com

1.4. Emergency telephone number

Emergency telephone	UK - 00 44 (0) 161 866 4800 Office hrs = 0900 - 1700 hrs
National emergency telephone number	National Poisons Information Service City Hospital, Birmingham B187QH, United Kingdom Telephone: +44 121 507 4123 Email: allistervale@npis.org, sallybradberry@npis.org www.npis.org

SECTION 2: Hazards identification


2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards	Aerosol 1 - H222, H229
Health hazards	Skin Irrit. 2 - H315 STOT SE 3 - H336
Environmental hazards	Aquatic Chronic 3 - H412

2.2. Label elements

Hazard pictograms



Holts Headlight Sealer

Signal word	Danger
Hazard statements	H222 Extremely flammable aerosol. H229 Pressurised container: may burst if heated. H315 Causes skin irritation. H336 May cause drowsiness or dizziness. H412 Harmful to aquatic life with long lasting effects.
Precautionary statements	P102 Keep out of reach of children. P101 If medical advice is needed, have product container or label at hand. P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211 Do not spray on an open flame or other ignition source. P251 Do not pierce or burn, even after use. P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. P501 Dispose of contents/ container in accordance with national regulations.
Supplemental label information	EUH066 Repeated exposure may cause skin dryness or cracking.
UFI	UFI: PPA6-E0XS-F009-VR5E
Contains	Naphtha (petroleum), hydrotreated light
Detergent labelling	15 - < 30% aliphatic hydrocarbons, Contains CITRAL, d-limonene
Supplementary precautionary statements	P403+P233 Store in a well-ventilated place. Keep container tightly closed. P405 Store locked up.

2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

BUTANE	30-60%
CAS number: 106-97-8	EC number: 203-448-7
	REACH registration number: 01-2119474691-32-XXXX
Classification	
Flam. Gas 1 - H220	
Press. Gas	
Naphtha (petroleum), hydrotreated light	10-30%
CAS number: 64742-49-0	EC number: 265-151-9
	REACH registration number: 01-2119475133-43-XXXX
Classification	
Flam. Liq. 2 - H225	
Skin Irrit. 2 - H315	
STOT SE 3 - H336	
Asp. Tox. 1 - H304	
Aquatic Chronic 2 - H411	

Holts Headlight Sealer

PROPANE		10-30%
CAS number: 74-98-6	EC number: 200-827-9	REACH registration number: 01-2119486944-21-XXXX
Classification		
Flam. Gas 1 - H220		
ISOBUTANE		10-30%
CAS number: 75-28-5	EC number: 200-857-2	REACH registration number: 01-2119486944-21-XXXX
Classification		
Flam. Gas 1 - H220 Press. Gas		

The full text for all hazard statements is displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information	Move affected person to fresh air at once. Get medical attention if any discomfort continues.
Inhalation	Move affected person to fresh air at once. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. Keep affected person warm and at rest. Get medical attention if any discomfort continues.
Ingestion	Not relevant.
Skin contact	Wash skin thoroughly with soap and water. Get medical attention if any discomfort continues.
Eye contact	Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.

4.2. Most important symptoms and effects, both acute and delayed

General information	The severity of the symptoms described will vary dependent on the concentration and the length of exposure.
Inhalation	Drowsiness, dizziness, disorientation, vertigo.
Ingestion	Due to the physical nature of this product, it is unlikely that ingestion will occur.
Skin contact	Causes skin irritation. Prolonged and frequent contact may cause redness and irritation.
Eye contact	No specific symptoms known. May cause temporary eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor	Treat symptomatically.
-----------------------------	------------------------

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	Extinguish with the following media: Powder. Dry chemicals, sand, dolomite etc. Water spray, fog or mist.
-------------------------------------	---

5.2. Special hazards arising from the substance or mixture

Specific hazards	Containers can burst violently or explode when heated, due to excessive pressure build-up. May explode when heated or when exposed to flames or sparks. Extremely flammable.
-------------------------	--

Holts Headlight Sealer

Hazardous combustion products Thermal decomposition or combustion products may include the following substances: Oxides of carbon.

5.3. Advice for firefighters

Protective actions during firefighting Containers close to fire should be removed or cooled with water. Use water to keep fire exposed containers cool and disperse vapours.

Special protective equipment for firefighters Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Wear protective clothing as described in Section 8 of this safety data sheet.

6.2. Environmental precautions

Environmental precautions Not considered to be a significant hazard due to the small quantities used.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Wear suitable protective equipment, including gloves, goggles/face shield, respirator, boots, clothing or apron, as appropriate. Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation. Leave small quantities to evaporate, if safe to do so. Do not allow material to enter confined spaces, due to the risk of explosion. If leakage cannot be stopped, evacuate area.

6.4. Reference to other sections

Reference to other sections Wear protective clothing as described in Section 8 of this safety data sheet. See Section 11 for additional information on health hazards. For waste disposal, see Section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Keep away from heat, sparks and open flame. Avoid spilling. Provide adequate ventilation. Avoid inhalation of vapours. Use approved respirator if air contamination is above an acceptable level. Avoid contact with skin and eyes.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Do not expose to temperatures exceeding 50°C/122°F. Keep in a cool, well ventilated place.

Storage class Flammable compressed gas storage.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure controls/Personal protection

8.1. Control parameters

Occupational exposure limits

BUTANE

Long-term exposure limit (8-hour TWA): WEL 600 ppm 1450 mg/m³

Short-term exposure limit (15-minute): WEL 750 ppm 1810 mg/m³

ISOBUTANE

Long-term exposure limit (8-hour TWA): OES 800 ppm

Short-term exposure limit (15-minute): OES 800 ppm

WEL = Workplace Exposure Limit.

Holts Headlight Sealer

Naphtha (petroleum), hydrotreated light (CAS: 64742-49-0)

DNEL

Workers - Inhalation; Long term systemic effects: 5306 mg/m³
 Workers - Dermal; Long term systemic effects: 13964 mg/kg/day
 General population - Inhalation; Long term systemic effects: 1131 mg/m³
 General population - Dermal; Long term systemic effects: 1377 mg/kg/day
 General population - Oral; Long term systemic effects: 1301 mg/kg/day

8.2. Exposure controls

Protective equipment



Appropriate engineering controls

Provide adequate general and local exhaust ventilation.

Eye/face protection

Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. The following protection should be worn: Chemical splash goggles or face shield.

Hand protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. It is recommended that gloves are made of the following material: Rubber (natural, latex). To protect hands from chemicals, gloves should comply with European Standard EN374.

Other skin and body protection

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact.

Hygiene measures

Use engineering controls to reduce air contamination to permissible exposure level. Do not smoke in work area. Wash at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. Do not eat, drink or smoke when using this product.

Respiratory protection

No specific recommendations. Respiratory protection must be used if the airborne contamination exceeds the recommended occupational exposure limit.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	Aerosol.
Colour	Yellow.
Odour	Lemon.
pH	Not applicable.
Melting point	Not applicable.
Initial boiling point and range	Not applicable.
Flash point	< 0°C
Vapour pressure	Not applicable.
Relative density	0.727 @ 20°C
Solubility(ies)	Immiscible with water.
Viscosity	Not determined.

Holts Headlight Sealer

9.2. Other information

Other information	None.
Refractive index	Not determined.
Particle size	Not applicable.
Molecular weight	Not applicable.
Volatile organic compound	This product contains a maximum VOC content of ca. 90 %.

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity	There are no known reactivity hazards associated with this product.
------------	---

10.2. Chemical stability

Stability	Stable at normal ambient temperatures.
-----------	--

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions	Avoid heat.
------------------------------------	-------------

10.4. Conditions to avoid

Conditions to avoid	Avoid heat, flames and other sources of ignition. Avoid contact with the following materials: Strong oxidising agents. Strong alkalis. Strong mineral acids.
---------------------	---

10.5. Incompatible materials

Materials to avoid	Strong alkalis. Strong mineral acids. Strong oxidising agents.
--------------------	--

10.6. Hazardous decomposition products

Hazardous decomposition products	Thermal decomposition or combustion products may include the following substances: Oxides of carbon.
----------------------------------	--

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Toxicological effects	No information available.
-----------------------	---------------------------

Acute toxicity - oral

Notes (oral LD ₅₀)	Based on available data the classification criteria are not met.
--------------------------------	--

Acute toxicity - dermal

Notes (dermal LD ₅₀)	Based on available data the classification criteria are not met.
----------------------------------	--

Acute toxicity - inhalation

Notes (inhalation LC ₅₀)	Based on available data the classification criteria are not met.
--------------------------------------	--

Skin corrosion/irritation

Skin corrosion/irritation	Causes skin irritation.
---------------------------	-------------------------

Serious eye damage/irritation

Serious eye damage/irritation	Based on available data the classification criteria are not met.
-------------------------------	--

Respiratory sensitisation

Respiratory sensitisation	Based on available data the classification criteria are not met.
---------------------------	--

Skin sensitisation

Holts Headlight Sealer

Skin sensitisation	Based on available data the classification criteria are not met.
<u>Germ cell mutagenicity</u>	
Genotoxicity - in vitro	Based on available data the classification criteria are not met.
Genotoxicity - in vivo	Based on available data the classification criteria are not met.
<u>Carcinogenicity</u>	
Carcinogenicity	Based on available data the classification criteria are not met.
<u>Reproductive toxicity</u>	
Reproductive toxicity - fertility	Based on available data the classification criteria are not met.
<u>Specific target organ toxicity - single exposure</u>	
STOT - single exposure	Central and/or peripheral nervous system damage.
<u>Specific target organ toxicity - repeated exposure</u>	
STOT - repeated exposure	Based on available data the classification criteria are not met.
<u>Aspiration hazard</u>	
Aspiration hazard	Not relevant.
<u>Inhalation</u>	
Inhalation	May cause respiratory system irritation. Vapours may cause headache, fatigue, dizziness and nausea. Prolonged inhalation of high concentrations may damage respiratory system.
<u>Ingestion</u>	
Ingestion	No harmful effects expected from quantities likely to be ingested by accident.
<u>Skin contact</u>	
Skin contact	Product has a defatting effect on skin. Prolonged contact may cause dryness of the skin. Causes skin irritation.
<u>Eye contact</u>	
Eye contact	Vapour or spray in the eyes may cause irritation and smarting.
<u>Acute and chronic health hazards</u>	
Acute and chronic health hazards	No specific long-term effects known.
<u>Route of exposure</u>	
Route of exposure	Inhalation Skin and/or eye contact

Toxicological information on ingredients.

BUTANE

Acute toxicity - oral

Acute toxicity oral (LD₅₀ mg/kg) 5,000.0

Species Rat

PROPANE

Acute toxicity - oral

Acute toxicity oral (LD₅₀ mg/kg) 5,000.0

Species Rat

ATE oral (mg/kg) 5,000.0

ISOBUTANE

Acute toxicity - oral

Holts Headlight Sealer

Acute toxicity oral (LD₅₀ mg/kg)	5,000.0
Species	Rat
ATE oral (mg/kg)	5,000.0

SECTION 12: Ecological information

Ecotoxicity Harmful to aquatic life with long lasting effects.

12.1. Toxicity

Acute aquatic toxicity

Acute toxicity - fish Not available.

Acute toxicity - aquatic invertebrates Not available.

Acute toxicity - aquatic plants Not available.

Acute toxicity - microorganisms Not available.

Acute toxicity - terrestrial Not available.

Chronic aquatic toxicity

Chronic toxicity - fish early life stage Not available.

Short term toxicity - embryo and sac fry stages Not available.

Chronic toxicity - aquatic invertebrates Not available.

12.2. Persistence and degradability

Persistence and degradability Expected to be readily biodegradable.

Phototransformation Not available.

Stability (hydrolysis) Not available.

Biodegradation Expected to be readily biodegradable.

Biological oxygen demand Not available.

Chemical oxygen demand Not available.

12.3. Bioaccumulative potential

Bioaccumulative potential The product does not contain any substances expected to be bioaccumulating.

12.4. Mobility in soil

Mobility The product contains volatile organic compounds (VOCs) which will evaporate easily from all surfaces.

Adsorption/desorption coefficient Not available.

Henry's law constant Not available.

Surface tension Not available.

12.5. Results of PBT and vPvB assessment

Holts Headlight Sealer

Results of PBT and vPvB assessment This product does not contain any substances classified as PBT or vPvB.

12.6. Other adverse effects

Other adverse effects None known.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal methods Empty containers must not be punctured or incinerated because of the risk of an explosion. Dispose of contents/container in accordance with local regulations.

SECTION 14: Transport information

General Refer to the Dangerous Goods List for information on any Special Provisions 190, 327, 344, 625.

14.1. UN number

UN No. (ADR/RID) 1950

UN No. (IMDG) 1950

UN No. (ICAO) 1950

UN No. (ADN) 1950

14.2. UN proper shipping name

Proper shipping name (ADR/RID) AEROSOLS

Proper shipping name (IMDG) AEROSOLS

Proper shipping name (ICAO) AEROSOLS

Proper shipping name (ADN) AEROSOLS

14.3. Transport hazard class(es)

ADR/RID class 2.1

ADR/RID classification code 5F

ADR/RID label 2.1

IMDG class 2.1

ICAO class/division 2.1

ADN class 2.1

Transport labels



14.4. Packing group

Not applicable.

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant
No.

Holts Headlight Sealer

14.6. Special precautions for user

EmS	F-D, S-U
ADR transport category	2
Tunnel restriction code	(D)

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation	Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended). Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended). Commission Regulation (EU) No 2015/830 of 28 May 2015. Regulation (EC) No 648/2004 of the European Parliament and of the Council of 31 March 2004 on detergents (as amended). Council Directive of 20 May 1975 on the approximation of the laws of the Member States relating to aerosol dispensers (75/324/EEC) (as amended).
Authorisations (Annex XIV Regulation 1907/2006)	No specific authorisations are known for this product.
Restrictions (Annex XVII Regulation 1907/2006)	No specific restrictions on use are known for this product.

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

Holts Headlight Sealer

Abbreviations and acronyms used in the safety data sheet	<p>ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways.</p> <p>ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.</p> <p>ATE: Acute Toxicity Estimate.</p> <p>BOD: Biochemical Oxygen Demand.</p> <p>CAS: Chemical Abstracts Service.</p> <p>DMEL: Derived Minimal Effect Level.</p> <p>DNEL: Derived No Effect Level.</p> <p>EC₅₀: 50% of maximal Effective Concentration.</p> <p>GHS: Globally Harmonized System.</p> <p>IATA: International Air Transport Association.</p> <p>ICAO: Technical Instructions for the Safe Transport of Dangerous Goods by Air.</p> <p>IMDG: International Maritime Dangerous Goods.</p> <p>LC₅₀: Lethal Concentration to 50 % of a test population.</p> <p>LD₅₀: Lethal Dose to 50% of a test population (Median Lethal Dose).</p> <p>PBT: Persistent, Bioaccumulative and Toxic substance.</p> <p>REACH: Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006.</p> <p>SVHC: Substances of Very High Concern.</p> <p>vPvB: Very Persistent and Very Bioaccumulative.</p>
Revision date	26/05/2020
Revision	3
Supersedes date	21/11/2017
SDS number	21201
Hazard statements in full	<p>H220 Extremely flammable gas.</p> <p>H222 Extremely flammable aerosol.</p> <p>H225 Highly flammable liquid and vapour.</p> <p>H229 Pressurised container: may burst if heated.</p> <p>H304 May be fatal if swallowed and enters airways.</p> <p>H315 Causes skin irritation.</p> <p>H336 May cause drowsiness or dizziness.</p> <p>H411 Toxic to aquatic life with long lasting effects.</p> <p>H412 Harmful to aquatic life with long lasting effects.</p>