

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 17.03.2017

Version number 4

Revision: 17.03.2017

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name:** Motip-LS-Primer grau
- **Article number:** M900101
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
- **Sector of Use SU21** Consumer uses: Private households / general public / consumers
- **Product category PC9a** Coatings and paints, thinners, paint removers
- **Application of the substance / the mixture** Paint
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
MOTIP DUPLI GmbH
Kurt Vogelsang Strasse 6
D-74855 Haßmersheim
Tel.: +49/6266/75-0
msds@de.motipdupli.com
- **Further information obtainable from:** Department Product Safety
- **1.4 Emergency telephone number:**
Tel.: +49 6266-75-310
Fax +49 6266-75-362
(Mo - Th 08:00 am - 04:00 pm, Fr 08:00 am - 00:30 pm)

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



GHS02 flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



GHS09 environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



GHS07

Eye Irrit. 2 H319 Causes serious eye irritation.
STOT SE 3 H336 May cause drowsiness or dizziness.

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**
The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 17.03.2017

Version number 4

Revision: 17.03.2017

Trade name: **Motip-LS-Primer grau**

(Contd. of page 1)

· **Hazard pictograms**

GHS02 GHS07 GHS09

· **Signal word** *Danger*· **Hazard-determining components of labelling:**

n-butyl acetate
acetone

· **Hazard statements**

H225 Highly flammable liquid and vapour.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
H411 Toxic to aquatic life with long lasting effects.

· **Precautionary statements**

P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260 Do not breathe vapours.
P271 Use only outdoors or in a well-ventilated area.
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P405 Store locked up.
P501 Dispose of contents / container in accordance with regional regulations.

· **Additional information:**

EUH066 Repeated exposure may cause skin dryness or cracking.

· **2.3 Other hazards**· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.
· **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

· **3.2 Chemical characterisation: Mixtures**

· **Description:** Mixture of substances listed below with nonhazardous additions.

· **Dangerous components:**

CAS: 123-86-4 EINECS: 204-658-1 Index number: 607-025-00-1 Reg.nr.: 01-2119485493-29	<i>n</i> -butyl acetate ⚠ Flam. Liq. 3, H226 ⚠ STOT SE 3, H336	25-<50%
CAS: 67-64-1 EINECS: 200-662-2 Index number: 606-001-00-8 Reg.nr.: 01-2119471330-49	acetone ⚠ Flam. Liq. 2, H225 ⚠ Eye Irrit. 2, H319; STOT SE 3, H336	12.5-<20%
CAS: 9004-70-0	cellulose nitrate ⚠ Flam. Sol. 1, H228	5-<10%
CAS: 7779-90-0 EINECS: 231-944-3 Index number: 030-011-00-6 Reg.nr.: 01-2119485044-40	trizinc bis(orthophosphate) ⚠ Aquatic Acute 1, H400; Aquatic Chronic 1, H410	2.5-<5.0%

(Contd. on page 3)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 17.03.2017

Version number 4

Revision: 17.03.2017

Trade name: Motip-LS-Primer grau

(Contd. of page 2)

CAS: 1330-20-7 EINECS: 215-535-7 Index number: 601-022-00-9 Reg.nr.: 01-2119555267-33	Xylol Flam. Liq. 3, H226 STOT RE 2, H373; Asp. Tox. 1, H304 Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	2.5-<5.0%
CAS: 64-17-5 EINECS: 200-578-6 Index number: 603-002-00-5 Reg.nr.: 01-2119457610-43	ethanol Flam. Liq. 2, H225	2.5-<5.0%
CAS: 108-65-6 EINECS: 203-603-9 Index number: 607-195-00-7 Reg.nr.: 01-2119475791-29	2-methoxy-1-methylethyl acetate Flam. Liq. 3, H226	2.5-<5.0%
CAS: 546-93-0	Magnesite substance with a Community workplace exposure limit	<2.5%
CAS: 100-41-4 EINECS: 202-849-4 Index number: 601-023-00-4 Reg.nr.: 01-2119489370-35	ethylbenzene Flam. Liq. 2, H225 STOT RE 2, H373; Asp. Tox. 1, H304 Acute Tox. 4, H332 Aquatic Chronic 3, H412	<2.5%
CAS: 2687-91-4 EINECS: 220-250-6 Index number: 616-208-00-5	N-Ethyl-2-Pyrrolidone Repr. 1B, H360D	≤0.5%
CAS: 1314-13-2 EINECS: 215-222-5 Index number: 030-013-00-7 Reg.nr.: 01-2119463881-32	zinc oxide Aquatic Acute 1, H400; Aquatic Chronic 1, H410	≤0.5%

Additional information:

The content of Benzene (EINECS-Nr. 200-753-7) in the ingredients is less than 0,1% (Note P Annex 1A 1272/2008 EU), so the classification as carcinogen need not to apply.

For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures**4.1 Description of first aid measures**

· **After inhalation:** Supply fresh air; consult doctor in case of complaints.

· **After skin contact:** Generally the product does not irritate the skin.

· **After eye contact:**

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· **After swallowing:** Drink plenty of water and provide fresh air. Call for a doctor immediately.

· **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.

· **4.3 Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

SECTION 5: Firefighting measures**5.1 Extinguishing media**

· **Suitable extinguishing agents:**

CO₂, powder or water spray. Larger fires with water spray or foam. Cool containers with water

· **For safety reasons unsuitable extinguishing agents:** Water with full jet

· **5.2 Special hazards arising from the substance or mixture** No further relevant information available.

· **5.3 Advice for firefighters -**

(Contd. on page 4)

GB

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 17.03.2017

Version number 4

Revision: 17.03.2017

Trade name: **Motip-LS-Primer grau**

(Contd. of page 3)

· **Protective equipment:** No special measures required.

SECTION 6: Accidental release measures

· **6.1 Personal precautions, protective equipment and emergency procedures**

Wear protective equipment. Keep unprotected persons away.

· **6.2 Environmental precautions:**

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

Do not allow product to reach sewage system or any water course.

Prevent seepage into sewage system, workpits and cellars.

· **6.3 Methods and material for containment and cleaning up:**

Do not flush with water or aqueous cleansing agents

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Ensure adequate ventilation.

· **6.4 Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· **7.1 Precautions for safe handling**

Use only in well ventilated areas.

Ensure good ventilation/exhaustion at the workplace.

· **Information about fire - and explosion protection:**

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

· **7.2 Conditions for safe storage, including any incompatibilities**

· **Storage:**

· **Requirements to be met by storerooms and receptacles:** Store in a cool location.· **Information about storage in one common storage facility:** Not required.

· **Further information about storage conditions:**

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

· **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

· **Additional information about design of technical facilities:** No further data; see item 7.

· **8.1 Control parameters**

· **Ingredients with limit values that require monitoring at the workplace:**

123-86-4 n-butyl acetate

WEL Short-term value: 966 mg/m³, 200 ppmLong-term value: 724 mg/m³, 150 ppm

67-64-1 acetone

WEL Short-term value: 3620 mg/m³, 1500 ppmLong-term value: 1210 mg/m³, 500 ppm

64-17-5 ethanol

WEL Long-term value: 1920 mg/m³, 1000 ppm

(Contd. on page 5)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 17.03.2017

Version number 4

Revision: 17.03.2017

Trade name: Motip-LS-Primer grau

(Contd. of page 4)

108-65-6 2-methoxy-1-methylethyl acetate

WEL Short-term value: 548 mg/m³, 100 ppm
Long-term value: 274 mg/m³, 50 ppm
Sk

546-93-0 Magnesite

WEL Long-term value: 10* 4** mg/m³
*inhalable dust **respirable dust

100-41-4 ethylbenzene

WEL Short-term value: 552 mg/m³, 125 ppm
Long-term value: 441 mg/m³, 100 ppm
Sk

· **Additional information:** The lists valid during the making were used as basis.

· **8.2 Exposure controls**· **Personal protective equipment:**· **General protective and hygienic measures:**

-

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

· **Respiratory protection:**

Not necessary if room is well-ventilated.

Otherwise, filter class A / P2 or self contained.

Use suitable respiratory protective device in case of insufficient ventilation.

· **Protection of hands:**

In case of contact with spray dust protective gloves made of butyl should be used (min. 0.4 mm thick), e.g.

KCL Camatril, article no. 898 or similar products



Protective gloves

Solvent resistant gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves** Butyl rubber, BR· **Penetration time of glove material**

Butyl rubber gloves with a thickness of 0.4 mm are resistant to:

Acetone: 480 min

Butyl acetate: 60 min

Ethyl acetate: 170 min

Xylene: 42 min

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:** Safety glasses

SECTION 9: Physical and chemical properties

· **9.1 Information on basic physical and chemical properties**· **General Information**· **Appearance:**

Form: Fluid

Colour: According to product specification

(Contd. on page 6)

GB

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 17.03.2017

Version number 4

Revision: 17.03.2017

Trade name: **Motip-LS-Primer grau**

(Contd. of page 5)

· Odour:	Characteristic
· Odour threshold:	Not determined.
· pH-value:	Not determined.
· Change in condition	
Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range:	78 °C
· Flash point:	12 °C
· Flammability (solid, gas):	Not applicable.
· Ignition temperature:	180 °C
· Decomposition temperature:	Not determined.
· Auto-ignition temperature:	Product is not selfigniting.
· Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· Explosion limits:	
Lower:	1.2 Vol %
Upper:	13.0 Vol %
· Vapour pressure at 20 °C:	233 hPa
· Density at 20 °C:	0.9 g/cm ³
· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with water:	Not miscible or difficult to mix.
· Partition coefficient: n-octanol/water:	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic at 20 °C:	60 s (ISO 4 mm)
· Solvent content:	
VOC-(EU)	---
	524.2 g/l
· VOC-EU%	58.24 %
· Solids content:	21.9 %
· 9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

GB

(Contd. on page 7)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 17.03.2017

Version number 4

Revision: 17.03.2017

Trade name: **Motip-LS-Primer grau**

(Contd. of page 6)

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.

- **LD/LC50 values relevant for classification:**

123-86-4 n-butyl acetate

Oral	LD50	13100 mg/kg (rat)
Dermal	LD50	>5000 mg/kg (rabbit)
Inhalative	LC50/4 h	>21.0 mg/l (rat)

67-64-1 acetone

Oral	LD50	5800 mg/kg (rat)
Dermal	LD50	20000 mg/kg (rabbit)

7779-90-0 trizinc bis(orthophosphate)

Oral	LD50	>5000 mg/kg (rat)
------	------	-------------------

64-17-5 ethanol

Oral	LD50	7060 mg/kg (rat)
Inhalative	LC50/4 h	20000 mg/l (rat)

108-65-6 2-methoxy-1-methylethyl acetate

Oral	LD50	8532 mg/kg (rat)
Dermal	LD50	>2000 mg/kg (rat)
Inhalative	LC50	134 mg/l (oncorhynchus mykiss / Regenbogenforelle) (OECD-Prüfrichtlinie 203)
	LC50/4 h	35.7 mg/l (rat)

100-41-4 ethylbenzene

Oral	LD50	3500 mg/kg (rat)
Dermal	LD50	17800 mg/kg (rabbit)

1314-13-2 zinc oxide

Oral	LD50	7950 mg/kg (mouse)
------	------	--------------------

- **Primary irritant effect:**
- **Skin corrosion/irritation** Based on available data, the classification criteria are not met.
- **Serious eye damage/irritation**
Causes serious eye irritation.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure**
May cause drowsiness or dizziness.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- **12.1 Toxicity**

- **Aquatic toxicity:**

108-65-6 2-methoxy-1-methylethyl acetate

EC 10	>1000 mg/l (bel) (ISO 8192)
EC50 / 48h	>500 mg/l (daphnia magna / Wasserfloh) (Richtlinie 67/548/EWG. Anhang V, C.2))
EC50/72h	>1000 mg/l (Selenastrum capricornutum) (OECD-Prüfrichtlinie 201)

(Contd. on page 8)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 17.03.2017

Version number 4

Revision: 17.03.2017

Trade name: Motip-LS-Primer grau

(Contd. of page 7)

NOEC	≥100 mg/l (<i>daphnia magna</i> / Wasserfloh) (OECD-Prüfrichtlinie 202)
	47.5 mg/l (<i>Oryzias latipes</i>) (OECD-Prüfrichtlinie 204)

- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Harmful to fish
- **Additional ecological information:**
- **General notes:**
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.
Harmful to aquatic organisms
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- **European waste catalogue**

08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances
15 01 04	metallic packaging

- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information

- **14.1 UN-Number**
- **ADR, IMDG, IATA** UN1263
- **14.2 UN proper shipping name**
- **ADR** UN1263 PAINT, ENVIRONMENTALLY HAZARDOUS
- **IMDG, IATA** PAINT

- **14.3 Transport hazard class(es)**

- **ADR**



- **Class** 3 (F1) Flammable liquids.
- **Label** 3

- **IMDG, IATA**



- **Class** 3 Flammable liquids.

(Contd. on page 9)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 17.03.2017

Version number 4

Revision: 17.03.2017

Trade name: Motip-LS-Primer grau

(Contd. of page 8)

· Label	3
· 14.4 Packing group · ADR, IMDG, IATA	II
· 14.5 Environmental hazards: · Marine pollutant: · Special marking (ADR):	Yes Symbol (fish and tree)
· 14.6 Special precautions for user · Danger code (Kemler): · EMS Number: · Stowage Category	Warning: Flammable liquids. 33 F-E, S-E B
· 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code	Not applicable.
· Transport/Additional information:	
· ADR · Limited quantities (LQ) · Excepted quantities (EQ)	5L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· Transport category · Tunnel restriction code	2 D/E
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	5L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· UN "Model Regulation":	UN 1263 PAINT, 3, II, ENVIRONMENTALLY HAZARDOUS

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3, 30
- **Waterhazard class:** Water hazard class 2 (Self-assessment): hazardous for water.
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**
- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H228 Flammable solid.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H360D May damage the unborn child.

(Contd. on page 10)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 17.03.2017

Version number 4

Revision: 17.03.2017

Trade name: Motip-LS-Primer grau

(Contd. of page 9)

H373 May cause damage to organs through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H412 Harmful to aquatic life with long lasting effects.

Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids – Category 2

Flam. Liq. 3: Flammable liquids – Category 3

Flam. Sol. 1: Flammable solids – Category 1

Acute Tox. 4: Acute toxicity – Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Repr. 1B: Reproductive toxicity – Category 1B

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3